

Atlantic Peristaltic Pump AT 50



The peristaltic technology conveys the material by “waving - moving - contractions” without squeezing or damaging it!

Advantages:

- ☑ Very Soft and Gentle material supply.
- ☑ Additional Socket for Agitator or Compressor.
- ☑ Infinitely Adjustable Pump Capacity.
- ☑ No Electronics.
- ☑ No Damage if Pump is running idle.
- ☑ For Solvent Resistant materials.
- ☑ Quick and easy cleaning.
- ☑ Very Low - Wear.

Fields of application:

- ☑ Artificial Resin Plasters up to Grain size 2 mm.
- ☑ Mineral Sealing Sludges
- ☑ Bitumen Coating
- ☑ Spray Plasters
- ☑ Decopearls / Styropearls.
- ☑ Fire Protection.
- ☑ Acoustic Plaster

ATLANTIC PERISTALTIC PUMP AT 50	
Models	AT 50
Motor	0.55 kW
Pump capacity	0 - 8.5 litre/min.
Max. Pressure	12 bar
Dimensions	800 x 460 x 890 mm
Grain Size	Max. 2.0 mm
Weight	55 kg

* All data is based on experience and dependent on the materials used. Machine design and construction are subject to technical modifications and upgrades.

DELIVERING MORE EFFICIENCY, FLEXIBILITY AND POWER



ACE CENTRO ENTERPRISES

P. O. Box 95325, Abu Dhabi - U.A.E.

T : +971 2 6737900

F : +971 2 6737800

E : sales@acecentro.com

W : www.acecentro.com

